

серия Y IP23 (общепромышленные)

пп	тип	P	Ин	соед	Z ₁ /Z ₂	Da	Di	L	δ	d	y	S	u	Nz	a
1	Y160M-2	15	29	△	36/28	290	160	100	0,8	1,06×2+1,12	1-14	6	6	24	1
2	Y160L1-2	18,5	36	△	36/28	290	160	125	0,8	1,4+1,5	1-14	6	6	20	1
3	Y160L2-2	22	42	△	36/28	290	160	135	0,8	1,5+1,6	1-14	6	6	18	1
4	Y180M-2	30	57	△	36/28	327	182	135	1,0	1,3×2	1-14	6	6	32	2
5	Y180L-2	37	70	△	36/28	327	182	160	1,0	1,4×2	1-14	6	6	27	2
6	Y200M-2	45	84	△	36/28	368	210	155	1,1	1,25×2+1,3×2	1-14	6	6	24	2
7	Y200L-2	55	103	△	36/28	368	210	185	1,1	1,4×3	1-14	6	6	21	2
8	Y225M-2	75	140	△	36/28	400	225	185	1,2	1,6×3	1-14	6	6	18	2
9	Y250S-2	90	167	△	42/34	445	225	170	1,5	1,3×2+1,4×3	1-16	7	6	6	2
10	Y250M-2	110	201	△	42/34	445	225	195	1,5	1,5×4+1,6	1-16	7	6	4	2
11	Y280M-2	132	241	△	42/34	493	280	200	1,6	1,5×6	1-16	7	6	12	2
12	Y160M-4	11	23	△	48/44	290	187	100	0,55	1,18	1-11	4	12	54	2
13	Y160L1-4	15	30	△	48/44	290	187	130	0,55	1,3	1-11	4	12	42	2
14	Y160L2-4	18,5	37	△	48/44	290	187	150	0,55	1,4+1,5	1-11	4	12	18	2
15	Y180M-4	22	43	△	48/44	327	210	135	0,65	1,12×2	1-11	4	12	36	2
16	Y180L-4	30	58	△	48/44	327	210	175	0,65	1,3×2	1-11	4	12	32	2
17	Y200M-4	37	71	△	48/44	368	245	155	0,7	1,12+1,18×2	1-11	4	12	26	2
18	Y200L-4	45	86	△	48/44	368	245	185	0,7	1,3×3	1-11	4	12	22	2
19	Y225M-4	55	104	△	48/44	400	260	185	0,8	1,25+1,3	1-12	4	12	40	4
20	Y250S-4	75	141	△	60/50	445	300	185	0,9	1,25×2+1,3×3	1-14	5	12	14	2
21	Y250M-4	90	168	△	60/50	445	300	215	0,9	1,25×4+1,3×2	1-14	5	12	12	2
22	Y280S-4	110	205	△	60/50	493	330	200	1,0	1,25×4	1-14	5	12	24	4
23	Y280M-4	132	245	△	60/50	493	330	240	1,0	1,4×4	1-14	5	12	20	4
24	Y160M-6	7,5	17	△	54/44	290	205	95	0,45	1,4	1-9	3	18	32	1
25	Y160L-6	11	25	△	54/44	290	205	125	0,45	1,18×2+1,3	1-9	3	18	24	1

пп	тип	P	ln	соед	Z ₁ /Z ₂	Da	Di	L	δ	d	y	S	u	Nz	a
26	Y180M-6	15	32	△	54/44	327	230	125	0,5	1,4	1-9	3	18	44	2
27	Y180L-6	18,5	38	△	54/44	327	230	155	0,5	1,06×2	1-9	3	18	36	2
28	Y200M-6	22	44	△	54/44	368	260	135	0,5	1,18×2	1-9	3	18	36	2
29	Y200L-6	30	59	△	54/44	368	260	165	0,5	1,3+1,4	1-9	3	18	30	2
30	Y225M-6	37	71	△	72/58	400	285	175	0,55	1,18+1,25	1-12	4	18	30	3
31	Y250S-6	45	87	△	72/58	445	325	165	0,65	1,4×2	1-12	4	18	28	3
32	Y250M-6	55	106	△	72/58	445	325	195	0,65	1,06×4	1-12	4	18	24	3
33	Y280S-6	75	143	△	72/58	493	360	185	0,7	1,4×3	1-12	4	18	22	3
34	Y280M-6	90	169	△	72/58	493	360	240	0,7	1,5×3	1-12	3 и 2	6 и 18	18	3
35	Y160M-8	5,5	14	△	54/50	290	205	95	0,45	1,0	1-7	3 и 2	6 и 18	42	1
36	Y160L-8	7,5	18	△	54/50	290	205	125	0,45	1,06	1-7	3 и 2	6 и 18	32	1
37	Y180M-8	11	26	△	54/44	327	230	125	0,5	0,9×2	1-7	3 и 2	6 и 18	56	2
38	Y180L-8	15	34	△	54/44	368	230	155	0,5	1,0×2	1-7	3 и 2	6 и 18	44	2
39	Y200M-8	18,5	41	△	54/50	368	260	135	0,5	1,6×2	1-7	3 и 2	6 и 18	44	2
40	Y200L-8	22	48	△	54/50	368	260	165	0,5	1,25×2	1-7	3	24	36	2
41	Y225M-8	30	63	△	72/58	400	285	175	0,55	1,4	1-9	3	24	50	4
42	Y250S-8	37	78	△	72/58	445	325	165	0,65	1,06+1,12	1-9	3	24	46	4
43	Y250M-8	45	94	△	72/58	445	325	195	0,65	1,18+1,25	1-9	3	24	38	4
44	Y280S-8	55	115	△	72/58	493	360	185	0,7	1,3+1,4	1-9	3	24	36	4
45	Y280M-8	75	154	△	72/58	493	360	240	0,7	1,5+1,6	1-9	3	24	28	4

серия Y IP44 (общепромышленные)

пп	тип	P	ln	соед	Z ₁ /Z ₂	Da	Di	L	δ	d	y	S	u	Nz	a
1	Y801-2	0,75	1,7	Y	18/16	120	67	65	0,3	0,63	2 (1-9, 2-10), 1 (11-18)	2 и 1	3 и 3	111	1
2	Y802-2	1,1	2,4	Y	18/16	120	67	80	0,3	0,71	2 (1-9, 2-10), 1 (11-18)	2 и 1	3 и 3	90	1
3	Y90S-2	1,5	3,3	Y	18/16	130	72	85	0,35	0,85	2 (1-9, 2-10), 1 (11-18)	2 и 1	3 и 3	74	1