

ОБМОТОЧНЫЕ ДАННЫЕ ЭЛЕКТРОДВИГАТЕЛЕЙ

Серия 5А, 5АИ

Тип	п об/м.	Р кВт	Ток А	U	Δ/ Y	N	d мм	y	a	M кг	Da	Di	L1	Z1	Кл. из.
5АИ63А14	1500	0,25	1,37/0,79	220/380	Δ/Y	190	0,40	5	1	-	110	65	54	24	F
5АИ71В6У3	1000	0,55	2,9/1,73	220/380	Δ/Y	85	0,56	5	1	1,35	111	68	100	36	F
5АИ80В6У2	1000	1,1	3,0	380	Y	65	0,71	7;5	1	-	132	90	117	36	F
5АИ80В4У2	1390	1,5	6,83/3,95	220/380	Δ/Y	68	0,74	5	1	-	130	79	107	24	F
5АИ80А2У3	3000	1,5	5,7/3,5	220/380	Δ/Y	74	0,56×2	9;7+7	1	-	122	68	94	18	F
5АИ80В4У3	1400	1.5	-	220/380	Δ/Y	70	0.74	5	1	-	-	-	-	24	F
5АИ80В2У3	3000	2,2	8,1/4,7	220/380	Δ/Y	55	0,65×2	9;7+7	1	-	120	67	120	18	F
5АИ100S2У35	3000	4,0	14,6/8,45	220/380	Δ/Y	25	0,80×2	11;9	1	1,8	160	72	138	24	F
5АИ100S2У3	3000	4,0	14,6/8,15	220/380	Δ/Y	25	0,80×2	11;9	2	1,8	162	86	136	24	F
5АИ100S2У3	3000	4,0	14,6/6,45	220/380	Δ/Y	19	0,90×2	11;9	1	2,0	152	84	180	24	F
5АИ100	1500	4,0	8,4	380	Y	28	0,90×2	11;9;7	1	-	174	106	120	36	F
5АИ112М4У3	1450	5,5	20,0/11,7	220/380	Δ/Y	26	1,06×2	9;7+7	1	-	188	124	126	36	F
5АИ112М4У3	1450	5,5	11,7	380	Y	24	1,06×2	9;7+7	1	4,2	190	120	125	36	F
5АИ112М2	3000	7,6	25,0/14,8	220/380	Δ/Y	17	0,95×3	15;13;11+13;11	1	-	176	98	140	30	F
5АИ132S6У3	965	5,5	22,0/12,9	220/380	Δ/Y	25	1,00×2	5	1	-	210	148	150	36	F
5АИ132S4У3	1500	7,5	26,9/15,6	220/380	Δ/Y	21	0,95×3	9;7+7	1	4,68	210	140	142	36	F
5АИ132М4У3	1500	11,0	39,6/23,1	220/380	Δ/Y	16	0,9×5	9;7+7	1	-	213	136	184	36	F
5АИ132М4У35	1500	11,0	38,2/22,1	220/380	Δ/Y	11	1,04×3	11;9;7	1	3,9	213	135	232	36	F
5АИ132М2У3	3000	11,0	37,8/21,8	220/380	Δ/Y	11	0,95×4	15;13;11+13;11	1	3,9	212	116	170	30	F
5АМХ132М2У3	2910	11,0	21,0	380	Y	29	1,12+1,06	17;15;13	2	-	220	124	130	36	F
5АИ160S6У3	1000	11,0	23,5/13,5	380/660	Δ/Y	28	0,95×3	5	1	6,8	260	179	170	36	F
5АМХ160М4	1500	18,5	63,0/36,5	220/380	Δ/Y	21;11;10	1,18×3	11;9;7	2	11,8	270	165	190	48	F
5АИ160М4У3	1450	18,5	35,0/20,2	380/660	Δ/Y	20	1,00×4	9;7+7	1	-	260	178	192	36	F
5А160S2У2	3000	15,0	-	380	Δ	24+24	1,10×2	13	2	-	260	140	143	36	F
5АИ160S2У3	2940	15,0	29,4/17,0	380/660	Δ/Y	21+21	0,95×2	13	2	-	260	150	145	36	F

5AMX160M2Y3	3000	18,5	60,5/35,0	220/380	Δ/Y	12+12	1,25×3	13	2	-	254	138	153	36	F
5A160M2Y3	2920	18,5	60,5/35,0	220/380	Δ/Y	13+12	1,25×3	13	2	12,6	261	140	150	36	F
5AИ180M2	3000	30,0	56,9/32,9	380/660	Δ/Y	13+13	1,00×4	12	2	15,0	290	165	215	36	F
5AMX180S2Y3	2930	22,0	71,5/41,5	220/380	Δ/Y	12+12	1,16×4	12	2	-	295	146	130	36	F
5A200M4Y3	1470	37,0	124,0/72,0	220/380	Δ/Y	7+8	1,18×6	10	2	20,0	329	207	205	48	F
5A225M4Y3	1500	55,0	-	220/380	Δ/Y	10+9	1,18×4	10	4	15,0	347	215	282	48	F
5AM250M4Y3	1500	90,0	164,0/94,0	380/660	Δ/Y	13+13	1,20×5	12	4	51,0	-	-	-	60	F
5AИ250M4Y2	1480	90,0	165,6/95,6	380/660	Δ/Y	13+13	1,40×4	10	4	43	400	282	350	48	F
5AИ250S2Y3	3000	75,0	134,6/77,5	380/660	Δ/Y	8+9	1,68×4	11	2	-	400	230	230	36	F
5AM280M4Y3	1480	132,0	241,0/139,0	380/660	Δ/Y	9+9	1,56×6	12	4	90,0	-	-	-	60	F
5A180M4	1460	30,0	98,0/57,0	220/380	Δ/Y	14	1,18×3+1,1×2	10	2	13,2	274	170	266	48	F
5AИ80B2	2820	2,2	8,62/4,99	220/380	Δ/Y	59	0,63×2	9;7+7	1	-	130	72	107	18	F
5A	3000	15,0	-	380/660	Δ/Y	21+21	0,95+0,9	13	2	7,2	260	150	135	36	F
5AM112M2Y3	2925	7,5	23,8/13,8	220/380	Δ/Y	18	1,06×2+1,12	17;15;13	1	5,7	190	110	130	36	F
5A160S4Y3	1450	15,0	51,0/30,0	220/380	Δ/Y	25;13;12	1,30×2	11;9;7	2	10,0	260	162	160	48	F
5AM112MB6Y3	950	4,0	15,5/9,2	220/380	Δ/Y	23	0,90×2	11;9;7	1	3,1	192	132	130	54	F
5AИ2006	980	30,0	50,5/34,4	380/660	Δ/Y	11+11	1,06×3	8	2	13,8	330	230	255	54	F
5A200M8Y0Y3	735	18,5	71,0/41,0	220/380	Δ/Y	19+19	1,06×2	7	4	15,6	330	235	205	72	F
5AИ100L2Y2	2870	5,5	19,0/11,0	220/380	Δ/Y	22	0,85+0,90	15;13;11+13;11	1	2,3	175	100	120	30	F
5AИ100L4Y2	1425	4,0	15,2/8,8	220/380	Δ/Y	28	0,83×2	8;8+7	1	2,4	175	110	120	36	F
5AИ132M2Y3	2930	11,0	37,6/21,8	220/380	Δ/Y	16	1,04×4	15;13;11+13;11	1	-	214	117	144	30	F
5A225M4Y3	1470	55,0	107,7/62,0	380/660	Δ/Y	17+17	1,06×3	11	4	20	375	245	265	48	F
5AИ112M4Y2	1440	5,5	20,8/12,0	220/380	Δ/Y	21	0,67×4	9;7+7	1	2,8	175	110	150	36	F
5AИ100S4Y2	1420	3,0	11,6/6,7	220/380	Δ/Y	35	0,67×2	9;7+7	1	2,3	160	97	120	36	F
5A200M6YПY3	975	22,0	44,5/26,0	380/660	Δ/Y	20+20	1,00×2	10	3	-	326	236	200	72	F
5AИ90L4Y3	1410	2,2	9,1/5,3	220/380	Δ/Y	45	0,63×2	5	1	-	133	90	155	24	F
5AИ80B2Y2	2840	2,2	8,0/4,6	220/380	Δ/Y	26+26	0,80	6	1	-	119	68	122	18	F
5AM250S2Y3	2960	75,0	132,/76,0	380/660	Δ/Y	9+8	1,50×6	14	2	44	439	233	215	48	F
5AM315S2	2970	160,0	278,0/160,0	380/660	Δ/Y	5+5	1,60×13	15	2	81	540	285	295	48	F

5AИ80A4Y2	1400	1,1	4,7/2,7	220/380	Δ/Y	81	0,71	5	1	1,2	121	75	95	24	F
5AИ132M4Y2	1445	11,0	22,3/130	380/660	Δ/Y	27	1,06×2	11;9;7	1	-	212	135	180	36	F
5A180	1500	22,0	-	380	Y	38	1,12×2	11;9	4	-	272	172	195	48	F
5AИ180S4	1460	22,0	41,7/24,0	380/660	Δ/Y	15+15	1,00+0,95	11	2	-	290	190	190	48	F
5A	1500	90,0	-	380/660	Δ/Y	14+13	1,20×5	11	4	46	405	260	320	48	F
5AИ200M4Y2	1470	37,0	68,4/39,4	380/660	Δ/Y	41;24;24	1,06+0,95	11;9;7	4	-	320	210	220	48	F
5AMX160M2Y3	2920	18,5	35/20	380/660	Δ/Y	18	1,12×2+1,06×2	17;15;13	1	9,24	252	140	145	36	F

Тип	п-1 об/мин.	P кВт	Ток А	U	.n	N	d мм	γ	Сл.	а	Da	Di	L1	Z1	
5AM112MA6	1000	3	8,08	380	1	28	1,18	1-8	2	1	191	132	105	54	
5AM112SA6	1000	3	8,08	380	2	32	0,85	1-10	1	1	225	154	80	54	
5AM112SB6	1000	4	9,83	380	2	26	0,95	1-10	1	1	225	154	100	54	
5A112MB6	1000	4	9,83	380	1	23	1,25	1-10	1	1	225	132	130	54	
5A160S6	1000	11	22,5	380	4	14	1,06	1-10	1	1	260	180	145	54	
5A160M6	1000	15	30	380	4	30	0,71	1-10	1	3	260	180	210	54	
5A180M6	1000	18,5	37,1	380	3	17	1,18	1-11	2	2	295	209	195	72	
5A200M6	1000	22	44,1	380	3	23	1,12	1-11	2	3		235	205	72	
5A200L6	1000	30	60,1	380	3	19	1,25	1-11	2	3		235	225	72	
5A225M6	1000	37	42,9	660	2	30	1,5	1-11	2	3	368	240	245	72	
5A225M6	1000	37	74,1	380	5	16	1,06	1-11	2	3	368	257	230	72	
5AM250S6	1000	45	90,1	380	4	17	1,32	1-11	2	3	437	317	180	72	

5AMH250S6	1000	55	63,8	660	2	28	1,5	1-11	2	3	437	317	180	72
5AM250M6	1000	55	110	380	4	15	1,4	1-11	2	3	437	317	200	72
5AMH250M6	1000	75	87	660	2	25	1,6	1-11	2	3	437	317	200	72
5AM280S6	1000	75	150	380	4	20	1,5	1-11	2	6	490	345	260	72
5AM280M6	1000	90	104	660	5	16	1,5	1-11	2	3	490	345	310	72
5AH280S6	1000	90	104	660	4	19	1,6	1-11	2	3	490	345	260	72
5AH280M6	1000	110	128	660	5	16	1,5	1-11	2	3	490	345	310	72
5AM315S6	1000	110	128	660	6	17	1,5	1-11	2	3	530	375	260	72
5AM315M6	1000	132	153	660	6	14	1,6	1-11	2	3	530	375	340	72
5AH315S6	1000	132	153	660	6	16	1,5	1-11	2	3	530	375	260	72
5AH315M6	1000	160	186	660	4	27	1,4	1-11	2	6	530	375	340	72
5A80B8	750	0,55	2,06	380	1	80	0,63	2c1-5;1c1-6	1	1		88	115	36
5AM112MA8	750	2,2	6,61	380	1	37	1,12	1-7	1	1	191	132	105	48
5AM112SA8	750	2,2	6,61	380	1	43	1,12	1-7	1	1	225	158	80	48
5AM112SB8	750	3,0	8,19	380	1	35	1,25	1-7	1	1	225	158	100	48
5A160S8	750	7,5	16,1	380	3	19	1,18	1-7	1	1	260	180	160	48
5A160M8	750	11,0	22,8	380	4	15	1,18	1-7	1	1	260	180	195	48
5A180M8	750	15,0	30,4	380	2	22	1,25	1-8	2	2	295	209	195	72

5A200M8	750	18,5	37,5	380	2	36	1,06	1-8	2	4	327	235	195	72
5A200L8	750	22,0	44,6	380	2	32	1,25	1-8	2	4		235	230	72
5A225M8	750	30,0	60,8	380	3	26	1,06	1-8	2	4	368	257	240	72
5AM250S8	750	37,0	75,0	380	3	26	1,25	1-8	2	4	437	317	180	72
5AM250M8	750	45,0	91,2	380	3	22	1,4	1-8	2	4	437	317	200	72
5AMH250S8	750	45,0	52,8	660	2	48	1,12	1-8	2	4	437	317	180	72
5AM280S8	750	55,0	64,5	660	3	36	1,32	1-8	2	4	490	355	240	72
5AMH250M8	750	55,0	64,5	660	2	40	1,25	1-8	2	4	437	317	220	72
5AH280S8	750	75,0	88,0	660	3	34	1,4	1-8	2	4	490	355	240	72
5AM280M8	750	75,0	152,0	380	5	16	1,6	1-8	2	4	490	355	330	72
5AM315S8	750	90,0	106,0	660	4	26	1,5	1-8	2	4	530	385	310	72
5AH280M8	750	90,0	106,0	660	3	26	1,6	1-8	2	4	490	355	330	72
5A315-8	750	110	129,0	660	4	22	1,5	1-8	2	4	530	385	375	72
5AM315M8	750	110,0	129,0	660	4	22	1,6	1-8	2	4	530	385	360	72
5AH315S8	750	132,0	155,0	660	4	24	1,5	1-8	2	4	530	385	310	72
5AH315M8	750	160,0	188,0	660	3	42	1,32	1-8	2	8	530	385	360	72
5AM315S12	500	45,0	92,3	380	3	30	1,32	1-7	2	6	530	405	260	90
5AM315M12	500	55,0	113,0	380	3	24	1,5	1-7	2	6	530	405	330	90

Тип	п-1 олб/мин	Р кВт.	Ток А	U	.n	N	D mm	γ	Сл	а	Da	Di	L1		Z1
5A180S2	3000	22	41,6	380	4	24	1,12	1-15	2	2	295	154	120		36
5A180M2	3000	30	56,7	380	5	18	1,18	1-15	2	2	295	154	160		36
5A200M2	3000	37	40,5	660	4	26	1,32	1-15	2	2	327	177	180		36
5A200M2	3000	37	70	380	6	16	1,18	1-12	2	2	327	177	180		36
5A200L2	3000	45	85,1	380	6	14	1,25	1-15	2	2	327	177	210		36
5A225M2	3000	55	104	380	9	12	1,18	1-13	2	2	327	195	215		36
5A225M2	3000	55	60,2	660	4	22	1,4	1-13	2	2	327	195	215		36
5AM250S2	3000	75	142	380	9	10	1,6	1-15	2	2	437	232	200		48
5AM250M2	3000	90	170	380	10	9	1,6	1-15	2	2	437	232	230		48
5AMH250M2	3000	110	120	660	6	15	1,6	1-15	2	2	437	232	230		48
5AM280M2	3000	132	145	660	8	10	1,5	1-16	2	2	490	265	270		48
5AH280S2	3000	160	175	660	9	11	1,6	1-16	2	2	490	265	270		48
5AM315S2	3000	160	175	660	13	10	1,5	1-16	2	2	530	288	270		48
5AMH315M2	3000	250	274	660	14	8	1,6	1-16	2	2	521	288	350		48
5AH315M2	3000	250	274	660	15	8	1,5	1-16	2	2	530	288	340		48
5A160M4	1500	18,5	36,2	380	4	21	1,06	1-11	2	2	260	160	185		48
5A180S4	1500	22	43	380	4	22	1,12	1-11	1	2	295	189	150		48
5A180M4	1500	30	58,7	380	5	17	1,12	1-11	1	2	295	189	200		48
5A200M4	1500	37	72,4	380	7	15	1,18	1-11	2	2	327	210	200		48
5A200M4	1500	37	41,9	660	4	27	1,12	1-11	2	2	327	210	200		48
5A200L4	1500	45	88,1	380	4	24	1,12	1-11	2	4	327	207	235		48
5A225M4	1500	55	108	380	3	24	1,5	1-11	2	4		235	230		48
5AM250S4	1500	75	147	380	6	17	1,32	1-12	2	4	437	290	225		60
5AM250M4	1500	90	176	380	7	14	1,32	1-12	2	4	437	290	270		60
5AMH250S4	1500	90	102	660	3	28	1,5	1-13	2	4	437	290	220		60
5AM250M4	1500	90	176	380	7	15	1,32	1-12	2	4	437	290	260		60
5AM280S4	1500	110	125	660	4	24	1,5	1-13	2	4	490	315	260		60

5AMH250M4	1500	110	125	660	4	24	1,4	1-13	2	4	437	290	260		60
5AM280M4	1500	132	150	660	6	18	1,4	1-13	2	4	490	315	360		60
5AH280S4	1500	132	150	660	5	24	1,5	1-13	2	4	490	315	260		60
5AM315S4	1500	160	181	660	5	20	1,6	1-13	2	4	530	340	315		60
5AH315S4	1500	200	227	660	8	18	1,5	1-13	2	4	530	340	315		60
5AH315M4	1500	250	283	660	8	16	1,6	1-12	2	4	530	340	390		60

Тип	п об/мин.	Р кВт	Ток А	U	Соединение фаз	N	d мм	у Шаг	a	М кг	Da	Di	L1	Z1	Кл. изол.
5AI63A14	1500	0,25	1,37/0,79	220/380	Δ/Y	190	0,40	5	1	-	110	65	54	24	F
5AI71B6Y3	1000	0,55	2,9/1,73	220/380	Δ/Y	85	0,56	5	1	1,35	111	68	100	36	F
5AI80B6Y2	1000	1,1	3,0	380	Y	65	0,71	7;5	1	-	132	90	117	36	F
5AI80B4Y2	1390	1,5	6,83/3,95	220/380	Δ/Y	68	0,74	5	1	-	130	79	107	24	F
5AI80A2Y3	3000	1,5	5,7/3,5	220/380	Δ/Y	74	0,56×2	9;7+7	1	-	122	68	94	18	F
5AI80B4Y3	1400	1.5	-	220/380	Δ/Y	70	0.74	5	1	-	-	-	-	24	F
5AI80B2Y3	3000	2,2	8,1/4,7	220/380	Δ/Y	55	0,65×2	9;7+7	1	-	120	67	120	18	F
5AI100S2Y35	3000	4,0	14,6/8,45	220/380	Δ/Y	25	0,80×2	11;9	1	1,8	160	72	138	24	F
5AI100S2Y3	3000	4,0	14,6/8,15	220/380	Δ/Y	25	0,80×2	11;9	2	1,8	162	86	136	24	F
5AI100S2Y3	3000	4,0	14,6/6,45	220/380	Δ/Y	19	0,90×2	11;9	1	2,0	152	84	180	24	F
5AI100	1500	4,0	8,4	380	Y	28	0,90×2	11;9;7	1	-	174	106	120	36	F
5AI112M4Y3	1450	5,5	20,0/11,7	220/380	Δ/Y	26	1,06×2	9;7+7	1	-	188	124	126	36	F
5AI112M4Y3	1450	5,5	11,7	380	Y	24	1,06×2	9;7+7	1	4,2	190	120	125	36	F
5AI112M2	3000	7,6	25,0/14,8	220/380	Δ/Y	17	0,95×3	15;13;11+13;11	1	-	176	98	140	30	F
5AI132S6Y3	965	5,5	22,0/12,9	220/380	Δ/Y	25	1,00×2	5	1	-	210	148	150	36	F
5AI132S4Y3	1500	7,5	26,9/15,6	220/380	Δ/Y	21	0,95×3	9;7+7	1	4,68	210	140	142	36	F
5AI132M4Y3	1500	11,0	39,6/23,1	220/380	Δ/Y	16	0,9×5	9;7+7	1	-	213	136	184	36	F

Тип	п об/мин.	Р кВт	Ток А	U	Соединение фаз	N	d мм	у Шаг	a	М кг	Da	Di	L1	Z1	Кл. изол.
5AI132M4Y35	1500	11,0	38,2/22,1	220/380	Δ/Y	11	1,04×3	11;9;7	1	3,9	213	135	232	36	F
5AI132M2Y3	3000	11,0	37,8/21,8	220/380	Δ/Y	11	0,95×4	15;13;11+13;11	1	3,9	212	116	170	30	F
5AMX132M2Y3	2910	11,0	21,0	380	Y	29	1,12+1,06	17;15;13	2	-	220	124	130	36	F
5AI160S6Y3	1000	11,0	23,5/13,5	380/660	Δ/Y	28	0,95×3	5	1	6,8	260	179	170	36	F
5AMX160M4	1500	18,5	63,0/36,5	220/380	Δ/Y	21;11;10	1,18×3	11;9;7	2	11,8	270	165	190	48	F
5AI160M4Y3	1450	18,5	35,0/20,2	380/660	Δ/Y	20	1,00×4	9;7+7	1	-	260	178	192	36	F
5A160S2Y2	3000	15,0	-	380	Δ	24+24	1,10×2	13	2	-	260	140	143	36	F
5AI160S2Y3	2940	15,0	29,4/17,0	380/660	Δ/Y	21+21	0,95×2	13	2	-	260	150	145	36	F
5AMX160M2Y3	3000	18,5	60,5/35,0	220/380	Δ/Y	12+12	1,25×3	13	2	-	254	138	153	36	F
5A160M2Y3	2920	18,5	60,5/35,0	220/380	Δ/Y	13+12	1,25×3	13	2	12,6	261	140	150	36	F
5AI180M2	3000	30,0	56,9/32,9	380/660	Δ/Y	13+13	1,00×4	12	2	15,0	290	165	215	36	F
5AMX180S2Y3	2930	22,0	71,5/41,5	220/380	Δ/Y	12+12	1,16×4	12	2	-	295	146	130	36	F
5A200M4Y3	1470	37,0	124,0/72,0	220/380	Δ/Y	7+8	1,18×6	10	2	20,0	329	207	205	48	F
5A225M4Y3	1500	55,0	-	220/380	Δ/Y	10+9	1,18×4	10	4	15,0	347	215	282	48	F
5AM250M4Y3	1500	90,0	164,0/94,0	380/660	Δ/Y	13+13	1,20×5	12	4	51,0	-	-	-	60	F
5AI250M4Y2	1480	90,0	165,6/95,6	380/660	Δ/Y	13+13	1,40×4	10	4	43	400	282	350	48	F
5AI250S2Y3	3000	75,0	134,6/77,5	380/660	Δ/Y	8+9	1,68×4	11	2	-	400	230	230	36	F
5AM280M4Y3	1480	132,0	241,0/139,0	380/660	Δ/Y	9+9	1,56×6	12	4	90,0	-	-	-	60	F
5A180M4	1460	30,0	98,0/57,0	220/380	Δ/Y	14	1,18×3+1,1×2	10	2	13,2	274	170	266	48	F
5AI80B2	2820	2,2	8,62/4,99	220/380	Δ/Y	59	0,63×2	9;7+7	1	-	130	72	107	18	F
5A	3000	15,0	-	380/660	Δ/Y	21+21	0,95+0,9	13	2	7,2	260	150	135	36	F
5AM112M2Y3	2925	7,5	23,8/13,8	220/380	Δ/Y	18	1,06×2+1,12	17;15;13	1	5,7	190	110	130	36	F
5A160S4Y3	1450	15,0	51,0/30,0	220/380	Δ/Y	25;13;12	1,30×2	11;9;7	2	10,0	260	162	160	48	F
5AM112MB6Y3	950	4,0	15,5/9,2	220/380	Δ/Y	23	0,90×2	11;9;7	1	3,1	192	132	130	54	F
5AI200_6	980	30,0	50,5/34,4	380/660	Δ/Y	11+11	1,06×3	8	2	13,8	330	230	255	54	F
5A200M8Y0Y3	735	18,5	71,0/41,0	220/380	Δ/Y	19+19	1,06×2	7	4	15,6	330	235	205	72	F
5AI100L2Y2	2870	5,5	19,0/11,0	220/380	Δ/Y	22	0,85+0,90	15;13;11+13;11	1	2,3	175	100	120	30	F

Тип	п об/мин.	Р кВт	Ток А	U	Соединение фаз	N	d мм	у Шаг	a	М кг	Da	Di	L1	Z1	Кл. изол.
5АИ100L4У2	1425	4,0	15,2/8,8	220/380	Δ/Y	28	0,83×2	8;8+7	1	2,4	175	110	120	36	F
5АИ132М2У3	2930	11,0	37,6/21,8	220/380	Δ/Y	16	1,04×4	15;13;11+13;11	1	-	214	117	144	30	F
5А225М4У3	1470	55,0	107,7/62,0	380/660	Δ/Y	17+17	1,06×3	11	4	20	375	245	265	48	F
5АИ112М4У2	1440	5,5	20,8/12,0	220/380	Δ/Y	21	0,67×4	9;7+7	1	2,8	175	110	150	36	F
5АИ100S4У2	1420	3,0	11,6/6,7	220/380	Δ/Y	35	0,67×2	9;7+7	1	2,3	160	97	120	36	F
5А200М6УПУ3	975	22,0	44,5/26,0	380/660	Δ/Y	20+20	1,00×2	10	3	-	326	236	200	72	F
5АИ90L4У3	1410	2,2	9,1/5,3	220/380	Δ/Y	45	0,63×2	5	1	-	133	90	155	24	F
5АИ80В2У2	2840	2,2	8,0/4,6	220/380	Δ/Y	26+26	0,80	6	1	-	119	68	122	18	F
5АМ250S2У3	2960	75,0	132,/76,0	380/660	Δ/Y	9+8	1,50×6	14	2	44	439	233	215	48	F
5АМ315S2	2970	160,0	278,0/160,0	380/660	Δ/Y	5+5	1,62×12	17	2	81	540	285	295	48	F
5АИ80А4У2	1400	1,1	4,7/2,7	220/380	Δ/Y	81	0,71	5	1	1,2	121	75	95	24	F
5АИ132М4У2	1445	11,0	22,3/130	380/660	Δ/Y	27	1,06×2	11;9;7	1	-	212	135	180	36	F
5А180	1500	22,0	-	380	Y	38	1,12×2	11;9	4	-	272	172	195	48	F